



Ultracoat[®] ReNewIt[™] Primer

Step 3

Two-Component Primer and Bonding Agent



DESCRIPTION

Ultracoat ReNewIt Primer is a proprietary, high-performance, two-component, water-based primer and bonding agent designed as the third step in preparing LVT, VCT, resilient, wood or bamboo flooring to be resurfaced with *Ultracoat HT 2K*.

FEATURES AND BENEFITS

- Enhances bond of recoat finishing systems
- Eliminates the traditional sanding required for recoating of existing flooring
- Dries quickly and does not change the floor color

WHERE TO USE

- To prime properly prepared LVT, VCT, wood and bamboo flooring before application of *Ultracoat HT 2K*

LIMITATIONS

- Do not dilute.
- Apply in temperatures between 50°F and 95°F (10°C and 35°C).
- Apply only to floors that have been cleaned using *Ultracoat ReNewIt Remover* and *Ultracoat ReNewIt Cleaner*.

SURFACE PREPARATION

- Thoroughly clean the flooring surface using *Ultracoat ReNewIt Remover* followed by a treatment of *Ultracoat ReNewIt Cleaner*. The flooring surface must be dry with no residue of either cleaning product remaining.

MIXING

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

1. Pour the entire contents of Part A into a clean mixing pail. Add the entire contents of Part B to the pail and mix for 2 to 3 minutes using a Jiffy mixer and drill motor at low to medium speed.
2. Let the product stand for 5 to 10 minutes.
3. Once mixed, *Ultracoat ReNewIt Primer* can only be used for 1 hour. It cannot be remixed.

Note: To avoid pressure buildup, do not reseal and store the mixture. Dispose of any remaining product in accordance with local, state/provincial and federal regulations. Decontaminate the empty Part B bottle before disposal by filling it with water, recapping it, shaking it and then discarding it.

PRODUCT APPLICATION

Read all instructions thoroughly before application.

1. Pour an *Ultracoat ReNewIt Primer* ribbon about 2" to 4" (5 to 10 cm) in width onto the surface of the prepared floor and spread it using a clean microfiber mop or T-bar at a very thin, uniform coat. Make sure to completely cover all areas that will receive final finish coats. Improper coverage of *Ultracoat ReNewIt Primer* may result in less than acceptable adhesion to the finish layer. The entire surface of the floor should appear to be wet with no dry spots. Do not allow the product to puddle.

Ultracoat[®] ReNewIt[®] Primer

2. Allow the applied product to dry for 1 hour using proper ventilation and air movement. Take caution not to introduce dust or debris. Apply *Ultracoat HT 2K* within 6 to 8 hours of applying *Ultracoat ReNewIt Primer*. If the primer cannot be covered by *Ultracoat HT 2K* within the window of 6 to 8 hours, a second application of primer is required.

CLEANUP

- Clean tools with soap and water while the primer is still fresh/wet.

PROTECTION

- Protect the primed floor from traffic, dirt and debris until it can be coated with *Ultracoat HT 2K*.

Product Characteristics

Laboratory Tests	Results
pH	7.3 to 7.9
Density (mixed product)	8.64 lbs. per U.S. gal. (1.04 g per cm ³)
Flash point	> 201°F (94°C)
VOCs (Rule #1113 of California's SCAQMD)	101 g per L
Solids content	25.07%

Shelf Life and Product Characteristics before mixing

Shelf life	1 year when stored in original, unopened packaging at 73°F (23°C)
Color	White when wet; dries clear
Storage conditions	50°F to 90°F (10°C to 32°C)

Protect containers from freezing in transit and storage. Provide for heated storage on site and deliver all materials at least 24 hours before work begins.

Packaging

Size
Kit: 1 U.S. gal. (3.79 L) Part A, Jug: 108.8 U.S. oz. (3.22 L) Part B, F-style can: 19.2 U.S. oz. (0.57 L)

Approximate Coverage*

Flooring Type	Coverage
LVT, VCT, resilient, hardwood and bamboo flooring	1,000 to 2,000 sq. ft. per U.S. gal. (24.5 to 49 m ² per L)

* Coverage shown is for estimating purposes only. Actual jobsite coverage may vary.

**Ultracoat
ReNewIt Primer**

Ultracoat ReNewit Primer



Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at

www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use,

and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

We proudly support the following industry organizations:



MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) /
(954) 246-8888

Technical Services

1-800-992-6273 (U.S. and Puerto Rico)
1-800-361-9309 (Canada)

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Services in Mexico

0-1-800-MX-MAPEI (0-1-800-696-2734)

Edition Date: January 11, 2023

MK 3000000 (22-3228)

For the most current product data and BEST-BACKED™ warranty information, visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.