



Ultracoat ReNewIt[®] Cleaner

Step 2

Spot-Free Cleaner and Rinsing Solution



DESCRIPTION

Ultracoat ReNewIt Cleaner is a high-performance, spot-free cleaning and rinsing solution designed to remove any remaining *Ultracoat ReNewIt Remover* and dirt as the second step in preparing LVT, VCT, resilient, wood or bamboo flooring to be recoated with floor finish. It can also be used as a general cleaner for all flooring types.

FEATURES AND BENEFITS

- Removes contaminants on the surface
- Ready to use, with no dilution required
- Leaves no residue

WHERE TO USE

- To clean and prepare LVT, VCT, resilient, wood and bamboo flooring after *Ultracoat ReNewIt Remover* application and before *Ultracoat ReNewIt Primer* placement for new wear-layer application
- For general cleaning of all flooring types

LIMITATIONS

- Do not dilute. *Ultracoat ReNewIt Cleaner* comes ready to use.
- Do not combine with *Ultracoat ReNewIt Remover*.
- Do not flood the flooring surface with the solution.
- Do not use as part of a recoating system for oil-treated or wax-finished floors.

SURFACE PREPARATION

- For recoating applications, the flooring surface must be first cleaned completely using *Ultracoat ReNewIt Remover*.
- For general cleaning, the flooring surface should be clean and free from loose dirt and debris. Vacuum the floor before cleaning.

MIXING

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

- No mixing is required. The product is ready to use.

PRODUCT APPLICATION

Read all installation instructions thoroughly before installation.

Manual Method

1. Pour *Ultracoat ReNewIt Cleaner* into a clean wash bucket.
2. Saturate a clean microfiber mop with the liquid. Mop the surface of the floor, rinsing the mop head often to avoid dirt buildup.
3. Repeat the above procedure until the entire floor has been cleaned. Clean or replace the microfiber mop head as necessary if it becomes overly contaminated, to avoid redepositing dirt on the surface.
4. Do not rinse the surface. *Ultracoat ReNewIt Cleaner* will not leave any residue on the surface.

Automatic Floor Scrubber Method

1. Pour *Ultracoat ReNewIt Cleaner* into the floor scrubber's solution tank.

**Ultracoat
ReNewIt Cleaner**

2. Follow the floor scrubber's operating procedures for proper use and clean the entire surface. For areas unreachable by the floor scrubber, follow the instructions above for the manual method. Do not rinse the surface.

PROTECTION

- Protect the cleaned floor from traffic, dirt and debris until it can be coated with *Ultracoat ReNewIt Primer*, followed by an application of *Ultracoat HT 2K*.

Product Performance Properties

Laboratory Tests	Results
pH	3.6 to 4.0
Density	8.3 lbs. per U.S. gal. (1 g per cm ³)
Flash point	> 212°F (100°C)
VOCs per the California Air Resources Board (CARB)	3.6% by weight
Freeze/thaw stability	Stable up to 3 cycles at 10°F (-12°C)

Shelf Life and Product Characteristics

Shelf life	1 year when stored in original, unopened packaging at 73°F (23°C)
Physical state	Liquid
Color	Clear yellow
Storage conditions	50°F to 90°F (10°C to 32°C)

Protect containers from freezing in transit and storage. Provide for heated storage on site and deliver all materials at least 24 hours before work begins.

Packaging

Size
Jug: 1 U.S. gal. (3.79 L)

Approximate Coverage*

Flooring Type	Coverage
LVT, VCT, resilient, wood and bamboo flooring	1,000 to 2,000 sq. ft. per U.S. gal. (24.5 to 49 m ² per L)

* Coverage shown is for estimating purposes only. Actual jobsite coverage may vary.

Ultracoat[®]
ReNewIt[®] Cleaner

Ultracoat ReNewit Cleaner



Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at

www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use,

and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

We proudly support the following industry organizations:



MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) /
(954) 246-8888

Technical Services

1-800-992-6273 (U.S. and Puerto Rico)
1-800-361-9309 (Canada)

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Services in Mexico

0-1-800-MX-MAPEI (0-1-800-696-2734)

Edition Date: January 11, 2023

MK 3000279 (22-3227)

For the most current product data and BEST-BACKED™ warranty information, visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.