


BRIDGFORD FLOORING SPECIFICATIONS

PRODUCT INFORMATION

CONSTRUCTION	Engineered Multi-Ply Core with 2mm White Oak Veneer
PLANK DIMENSIONS	1/2" Thickness x 7-1/2" Width x 75" Random Length
MILLING	4-sided Micro-Bevel Edge / Tongue and Groove
FINISH	Aluminer™ Aluminum Oxide Finish / Wire Brushed
COLOR VARIANCE	Wood is a natural product, thus colors and tones may vary.
RADIANT HEAT	Radiant floor heating compatible.
INSTALLATION	Nail, Staple or Glue. Above, on or below grade.
HARDNESS	Janka Hardness Rating of White Oak 1400
ENVIRONMENTAL	CARB II Compliant / LEED® Credits IEQ4.4 and MR6 / FloorScore® Certified



QUINCY 55790



ANDOVER 55791



FAIRHAVEN 55792




LITTLETON 55793




NEWBURY 55794



PRESCOTT 55795



AMHERST 55796



BUCKLAND 55797

PACKAGING

BOX WEIGHT: 59 LBS	SQFT PER BOX: 31.09	BOX DIMENSIONS: 4" x 7.8" x 75.2"
PLANKS PER BOX: Random	PACK SIZE: 45 Boxes/Pallet	PALLET DIMENSIONS: 44" x 40" x 76"

WARRANTY

FINISH	50-year Residential / 15-year Light Commercial
STRUCTURE	Lifetime Structural Warranty

RESOURCES

Download the latest versions of our installation and maintenance guides, as well as watch installation videos, at www.bhwfloors.com

