

Indestructible Plus 415 Extra Heavy Commercial Traffic



415 163
Natural Cream



415 117
Candlelight



415 118
Fairview Taupe



415 038
Silver Oak



415 056
Pewter Oak



415 007
Charcoal Oak



415 004
Ecru Oak



415 003
Weathered Oak



415 008
Umber Oak

Size

7.25" x 48" x 3 mm

Wear Layer

28 mil / UV-Cured Urethane

Embossing

RealTouch™ Embossed in Register

Edge Treatment

Beveled

Installation

Full Spread Adhesive

Packaging

14 pieces per carton (40 lbs)
33.8 SF per carton
55 cartons per pallet
20 pallets per container

Coordinating Moldings

See nextfloor.net for more details.

Product Classification

ASTM F1700 Class III, Type B

Testing

Critical Radiant Flux
Surface Flammability
Coefficient of Friction
Static Load Limit
Sound Transmission Class (STC)
Impact Insulation Class (IIC)
High Frequency Impact Insulation Class (HIIC) ASTM E3222
Floor Score Certified
Phthalate Free
100% Virgin PVC

ASTM E648 Class I
DOC FF 1-70 Passed
ASTM 2047 Passes > 0.6
ASTM F970 1300 lbs
ASTM E492 64
ASTM E989 69
ASTM E3222 89



Warranties

Lifetime Waterproof
Lifetime Residential Wear
30-Year Commercial Wear
See full warranty text at nextfloor.net

Recommended Adhesive

Next 1200™ 4GAL
NEXT1200-4GAL
4 gallon pail (34 pounds)
48 pails per pallet

Sample SKUs

Handle Boards

HB415RNF
5 per carton (59 lbs)

Strap Sets

SS415RNF
5 per carton (21.5 lbs)

Folders

3P415RNF
20 per carton (100 lbs)



nextfloor.net

07.09.24