

Level Best 433 Extra Heavy Commercial Traffic



Size

7.25" x 48" nominal (18.5 cm x 122 cm)
5 mm thick

Wear Layer

28 mil / UV-Cured Urethane
MCX™ MicroCeramic Reinforced Resin

Embossing

Real Touch™ Embossed in Register

Edge Treatment

Four-Sided Microbevel

Installation

Full Spread Adhesive
Recommended Adhesive: NEXT 1200™

Coordinating Moldings

See nextfloor.net for more details.

Packaging

9 pieces per carton (40 lbs)
21.8 SF per carton
50 cartons per pallet
20 pallets per container

Testing

Critical Radiant Flux
Surface Flammability
Coefficient of Friction
Static Load Limit
Sound Transmission Class (STC)
Impact Insulation Class (IIC)
High Frequency Impact Insulation Class(HIIC)
Floor Score Certified
Phthalate Free
100% Virgin PVC

ASTM E648	Class I
DOC FF 1-70	Passed
ASTM 204	Passes>0.6
ASTM F970	1200 lbs
ASTM E492	62
ASTM E989	57
ASTM E3222	89



Warranties

Lifetime Waterproof
Lifetime Residential Wear
40-Year Commercial Wear
Lifetime Transition Integrity*
*When installed beside Next Floor nylon carpet tile.
See full warranty text at nextfloor.net

Sample SKUs

Handle Boards

HB433NF
*includes Bandwidth Carpet
10 per carton (110 lbs)

Strap Sets

SS433NF
5 per carton (38.5 lbs)

Folders

2P433NF
*includes Bandwidth Carpet
20 per carton (60 lbs)

Extra Heavy Duty LVT

- 5 mm total thickness
- 28 mil wear layer
- MCX™ MicroCeramic protection
- 40-Year Commercial Warranty

