

Patina 419 Extra Heavy Commercial Traffic



419 006  
Silver Stria



419 015  
Antique Brass



419 016  
Antique Pewter



419 009  
Graphite Stria



419 017  
Antique Bronze

**Size**  
18" x 24" x 3 mm thick

**Wear Layer**  
28 mil / UV-Cured Urethane

**Edge Treatment**  
Beveled

**Installation**  
Full Spread Adhesive  
Recommended Adhesive: NEXT 1200™

**Packaging**  
11 pieces per carton (40 lbs)  
33 SF per carton  
60 cartons per pallet  
20 pallets per 20ft container

**Coordinating Moldings**  
See [nextfloor.net](http://nextfloor.net) for more details.

Testing	
Critical Radiant Flux	ASTM E648 Class I
Surface Flammability	DOC FF 1-70 Passed
Coefficient of Friction	ASTM 2047 Passes>0.6
Static Load Limit	ASTM F970 1300 lbs
Sound Transmission Class (STC)	ASTM E492 64
Impact Insulation Class (IIC)	ASTM E989 69
High Frequency Impact Insulation Class(HIIC)	ASTM E3222 89
Floor Score Certified	
Phthalate Free	
100% Virgin PVC	



**Product Classification**  
ASTM F1700 Class III, Type B

**Warranties**  
Lifetime Waterproof  
Lifetime Residential Wear  
30-Year Commercial Wear  
See [full warranty text at nextfloor.net](http://full warranty text at nextfloor.net)

**Sample SKUs**

**Handle Boards**  
HB419NF  
5 per carton (54 lbs)

**Folders**  
3P419NF  
20 per carton (78 lbs)