

# AIRGUARD®



## Premium Underlayment



**SUPERIOR MOISTURE PROTECTION**  
Unique AirFlow Technology releases trapped moisture as a vapor to prevent damage to your floors or subfloors.



**INDUSTRIAL-GRADE MOLD & MILDEW DEFENSE**  
The first underlayment to feature **MICROBAN** mold and mildew-fighting solution.



**EXCEEDS SOUND DAMPENING REQUIREMENTS**  
IIC 68, STC 67, DELTA IIC 20.




**RADIANT HEAT**  
Take the chill from your floors with added R-Value (.432). Ideal for use with radiant heat flooring.



**PREMIUM CUSHIONING & LEVELING**  
Soften the hardness of your floor's surface and eliminate minor subfloor imperfections.



**EASE OF INSTALLATION**  
Self-sealing lip and tape system help ensure the ultimate moisture barrier.



## PREMIUM MOISTURE, MOLD & MILDEW DEFENSE

ROBERTS® AirGuard® Premium Underlayment is rated #1 for use under laminate and engineered wood flooring. With superior advanced moisture protection, unparalleled mold / mildew defense, premium cushioning and superior sound control, no other underlayment even comes close.

### PRODUCT RATINGS\*

IIC  
68

STC  
67

R-Value  
0.432

Δ Delta  
20

made in  
**USA**



Scan here for  
PRODUCT  
INFORMATION



\* IIC measures sound such as moving furniture and walking, STC measures sound such as voices and television. Minimum IIC and STC sound rating requirement is 50 according to the International Building Code. R-Value is the rating used to measure resistance to heat flow. Δ Delta Rating is the only true measurement of sound reduction from a product (not a floor assembly) in the industry.

**#1 RATED** Underlayment for Laminate & Engineered Wood

**AIRGUARD**  
  
**Premium Underlayment**



**PRODUCT RATINGS\***

IIC  
68

STC  
67

Δ Delta  
20

R-Value  
0.432

**SPECIFICATIONS (+/-10%):**

<b>Material Composition</b>	Clear Film Bottom, Polyshim Center, Blue Moisture Barrier Top
<b>Thickness</b>	2 mm
<b>Compression Set</b>	ASTM D3574 - 6.3%
<b>Compression Strength</b>	ASTM D3574 - 4.7 PSI
<b>Indentation</b>	ASTM F1914 - 0.046" at 50lbs
<b>Smoke Density</b>	ASTM E662 - PASS
<b>Flammability Test</b>	ASTM D2859 (CPSC FF1-70) - PASS
<b>Thermal Resistance (R-Value)</b>	0.432
<b>Water Vapor Permeance</b>	ASTM E96 - 0.286 lbs/1000 ft <sup>2</sup> /24 hrs
<b>Antimicrobial Protection</b>	Fortified with MICROBAN® Antimicrobial Protection
<b>Installation Methods</b>	Floating
<b>Warranty</b>	Limited Lifetime Warranty

**AVAILABILITY (ROLL SIZES):**

Item #	70-105	70-105-300E	70-105-1
<b>Roll Size</b>	100 ft <sup>2</sup> (9.3 m <sup>2</sup> )	300 ft <sup>2</sup> (27.87 m <sup>2</sup> )	630 ft <sup>2</sup> (58.5 m <sup>2</sup> )
<b>Roll Width</b>	40" (1.02 m)	40" (1.02 m)	40" (1.02 m)
<b>Roll Length</b>	30' (9.14 m)	90' (27.43 m)	189' (57.61 m)

**Applications:**

Residential & commercial

**Approved Substrates:**


Cured concrete, interior plywood, & properly prepared OSB (skim coat may be required)

**Approved for Use Under:**

Laminate flooring & engineered wood flooring

**Locations:**

Below-grade, on-grade & above-grade



AirGuard®, ROBERTS® and logos are registered trademarks of Roberts Consolidated Industries, Inc., a wholly owned subsidiary of Q.E.P. Co., Inc. MICROBAN® trademark is owned by the Microban International, Ltd. and is used with permission.