

# **Safety Data Sheet**

Revision Date: 04/20/2021

# **SECTION 1:** Identification and Company Details

Product Name: 1550 MAXCOMPLETE

Product Code: 1550

Manufacturer/ Supplier: Roberts Consolidated Industries, Inc.

Address: 300 Cross Plains Blvd.

Dalton, GA 30721

Emergency Phone: (800) 424-9300 (24-hour Response / CHEMTREC)

Product Information: (706) 277-5294
Recommended Use: Adhesive

### SECTION 2: Hazard(s) Identification

# GHS classification in accordance with 29 CFR 1910.1200

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

**GHS** label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer by inhalation.

Precautionary Statements : **Prevention:** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

# **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

# SECTION 3: Composition / Information on Ingredients

#### **Mixtures**

#### Components

Chemical Name	CAS-No.	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreated	64742-48-9	Flam. Liq. 3: H226	≥1-<5
heavy		Asp. Tox. 1: H304	
Quartz (SiO <sub>2</sub> )	14808-60-7	Carc. 1A; H350i	≥ 0.1 - < 1
		STOT RE 1; H372	
		STOT SE 3; H335	
4,4'-methylenediphenyl diisocyanate	101-68-8	Acute Tox. 4; H332	≥ 0.1 - < 1
		Skin Irrit. 2; H315	
		Eye Irrit. 2B; H320	
		Resp. Sens. 1; H334	
		Skin Sens. 1; H317	
		STOT SE 3; H335	
		STOT RE 2; H373	

Actual concentration is withheld as a trade secret

# SECTION 4: First-Aid Measures

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

sensitizing effects
Asthmatic appearance
Allergic reactions

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause cancer by inhalation.

Notes to physician : Treat symptomatically.

# SECTION 5: Fire-Fighting Measures

Suitable extinguishing media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local

regulations.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

### SECTION 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### SECTION 7: Handling and Storage

Advice on protection against:

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory

disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.

Keep container tightly closed in a dry and well-ventilated place.

Observe label precautions.

Store in accordance with local regulations.

Further information on

storage stability

No decomposition if stored and applied as directed.

### SECTION 8: Exposure Control / Personal Protection

### Ingredients with workplace control parameters

<u>Components</u>	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	<u>Basis</u>
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	500 ppm	OSHA Z-1
			2,000 mg/m <sup>3</sup>	
		TWA	400 ppm	OSHA P0
			1,600 mg/m <sup>3</sup>	
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (respirable fraction)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable fraction)	0.025 mg/m³ (Silica)	ACGIH
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable fraction)	0.025 mg/m³ (Silica)	ACGIH
		TWA (respirable fraction)	0.025 mg/m³ (Silica)	ACGIH
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
			0.02 ppm	OSHA Z-1
		С	0.2 mg/m <sup>3</sup>	
		С	0.02 ppm	OCHY DO
		C	0.2 mg/m <sup>3</sup>	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits

**Engineering measures**: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants.

If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard

if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded,

self-contained breathing apparatus must be used.

Hand protection

Remarks

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times

when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this

is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances,

and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the product.

Remove contaminated clothing and protective equipment before entering eating areas.

Wash thoroughly after handling.

SECTION 9: Physical and Chemical Properties

Appearance : paste Color : various

Odor : hydrocarbon-like
Odor Threshold : No data available
pH : Not applicable
Melting point/range / Freezing point : No data available
Boiling point/boiling range : No data available

Flash point : 311 °F / 155 °C (Method: closed cup)

Evaporation rate : No data available Flammability (solid, gas) : No data available Upper explosion limit / Upper : No data available

flammability limit

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : 1.16 g/cm3 (73 °F / 23 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic :  $> 20.5 \text{ mm}^2/\text{s} (104 \text{ °F} / 40 \text{ °C})$ 

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : 53 g/l

(VOC) content

# SECTION 10: Stability and Reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available Incompatible materials : No data available

# SECTION 11: Toxicological Information

### **Acute toxicity**

Not classified based on available information.

### Components:

# 4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Test atmosphere: dust/mist Method: Expert judgment

### Skin corrosion/irritation

Not classified based on available information.

# Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# Germ cell mutagenicity

Not classified based on available information.

# Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

**OSHA** Not applicable

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

### Reproductive toxicity

Not classified based on available information.

# STOT-single exposure

Not classified based on available information.

# STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### **Aspiration toxicity**

Not classified based on available information.

### **Further information**

**Product:** Quartz (14808-60-7): This classification is relevant when ex-posed to Quartz (silicon dioxide) in dust or powder form

only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12: Ecological Information

### **Ecotoxicity**

No data available

### Persistence and degradability

No data available

# Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

Product:

Additional ecological information

Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal

of spilled material and runoff and contact with soil, waterways, drains and sewers.

# SECTION 13: Disposal Considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the

requirements of environmental protection and waste disposal legislation and any regional local

authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14: Transport Information

# International Regulations

### IATA-DGR

Not regulated as a dangerous good

### **IMDG-Code**

Not regulated as a dangerous good

# **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

# SECTION 15: Regulatory Information

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in

compliance with a TSCA Inventory exemption.

# **EPCRA - Emergency Planning and Community Right-to-Know**

# **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Carcinogenicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed

the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

www.P65Warnings.ca.gov

# SECTION 16: Other Information

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average OSHA P0 / TWA : 8-hour time weighted average

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-1 / C : Ceiling

OSHA Z-3 / TWA : 8-hour time weighted average

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

Prepared by: Roberts Consolidated Product Safety & Regulatory Compliance Group, (706) 277-5294

The information herein is given in good faith, but no warranty expressed or implied is made. Roberts Consolidated urges users of this product to evaluate its suitability and compliance with local regulations as Roberts Consolidated cannot foresee the final use of the product, nor the final location of usage.

Revision Date: 04/20/2021