







Reposado™ Pro

Classification ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile

Size* 7" x 48"(nom)
Overall Thickness* 2.5 mm

Wear Layer 20 mil featuring ouff Shield finish


Edge Square
Standard Colors 4 colors
Installation Method Glue-Down

Wear Limited Warranty Lifetime Residential / 30-Year Light Commercial Recycled Content This product does not contain recycled content.

Packaging 41.98 ft² (3.90 m²) per carton

18 pieces per carton 60 cartons per pallet

Weight Per Carton 38.42 lbs / 17.43 kg





















Product Testing

Chemical Resistance ASTM F 925 Passed

Critical Radiant Flux ASTM E 648 Class I, CRF ≥0.45

Dimensional Stability ASTM F 2199 Passed

Flavibility ASTM F 137 Passed

ASTM F 137 Flexibility Passed **ASTM F 1514** Passed Resistance to Heat **ASTM F 1515** Passed Resistance to Light ASTM E 662 Passed Smoke Density ASTM F 970 Static Load Limit Passed Thickness ASTM F 386 Passed



Paloma RPR-521



Sunrise RPR-522



Matador RPR-523



Siesta RPR-524

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit www.stcfloors.com for full product and warranty details.

EarthWerks® • 10850 Train Ct. • Houston, Texas 77041 • (800) 929-1222 • www.earthwerks.com

^{*}All measurements are nominal.