Safety Data Sheet ULTRABOND ECO 987 (NA)

Safety Data Sheet dated: 07/19/2024 - version 2 Date of first edition: 06/06/2024



1. IDENTIFICATION

Product identifier Mixture identification: Trade name: ULTRABOND ECO 987 (NA) Trade code: 9006578 Recommended use of the chemical and restrictions on use Recommended use: Adhesive Restrictions on use: Not available Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party Company: MAPEI CORP. (USA and Puerto Rico) 1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA Phone: 954-246-8888 Responsible: RDProductSafety@mapei.com Emergency 24 hour numbers: Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Eye irritation, Category 2A	Causes serious eye irritation.
Skin Sensitization, Category 1B	May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	May damage fertility or the unborn child if inhaled, in contact with skin and if swallowed.

Causes damage to organs through prolonged or repeated exposure if

inhaled, in contact with skin and if swallowed.

Specific target organ toxicity following repeated exposure, Category 1

Label elements

Hazard pictograms and Signal Word



Hazard statements

indiana otacom	
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child if inhaled, in contact with skin and if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Precautionary statements

P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
P260	Do not breathe mist/vapours/spray.	
P264	Wash skin thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P272	Contaminated work clothing must not be allowed out of the workplace.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy		

8 to do. Continue rinsing.

P308+P313 I	IF exposed or concerned:	Get medical advice/attention.
-------------	--------------------------	-------------------------------

- P314 Get medical advice/attention if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

List of components

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of com	iponents			
Qty	Name	Ident. Numb.	Classification	Registration Number
1-2.5 %	vinyltrimethoxysilane; Trimethoxyvinylsilane	CAS:2768-02-7 EC:220-449-8 Index:014-049- 00-0	Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Sens. 1B, H317	01-2119513215-52-XXXX
1-2.5 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350	
1-2.5 %	1-propanamine, 3- (trimethoxysilyl)-; 3- Aminopropyltrimethoxysilane	CAS:13822-56-5 EC:237-511-5	Skin Irrit. 2, H315; Eye Dam. 1, H318	01-2119510159-45-XXXX
0.25-0.49 %	oxirane, 2-[[3- (diethoxymethylsilyl)propoxy] methyl]-; Diethoxy(3- glycidyloxypropyl)methylsilane	CAS:2897-60-1 EC:220-780-8	Skin Sens. 1, H317	
0.25-0.49 %	dibutyltin diacetyldiacetonate; Dibutylbis(pentane-2,4-dionato- O,O')tin	CAS:22673-19-4 EC:245-152-0 Index:650-056- 00-0	STOT RE 1, H372; Repr. 1B, H360FD	01-2119557817-24-XXXX
0.1-0.25 %	bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate; Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4- piperidinyl) ester	EC:255-437-1	Skin Sens. 1, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Production Name

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL) OEL Country **Occupational Exposure Limit** Туре silica sand; quartz ACGIH Long Term: 0.025 mg/m3 CAS: 14808-60-7 A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis MAK AUSTRIA Long Term: 0.15 mg/m3 ACGIH Long Term: 0.025 mg/m3 (R), A2 - Pulm fibrosis, lung cancer MAK SWITZERLAN Long Term: 0.15 mg/m3 D FU Long Term: 0.1 mg/m3 Behaviour Binding dibutyltin MAK GERMANY Long Term: 0.02 mg/m3 - 0.004 ppm diacetyldiacetonate; Dibutylbis(pentane-2,4dionato-0,0')tin CAS: 22673-19-4 OSHA Long Term: 0.1 mg/m3 ACGIH Long Term: 0.1 mg/m3; Short Term: 0.2 mg/m3 "A4 - Not Classifiable as a Human Carcinogen" As Tin organic compounds [RR-00042-0];"Skin - potential significant contribution to overall exposure by the cutaneous route" As Tin organic compounds [RR-00042-0];"eye and upper respiratory tract irritation; headache; nausea; CNS and immune effects" As Tin organic compounds [RR-00042-0] MAK SWITZERLAN Long Term: 0.1 mg/m3 - 0.004 ppm D MAK SWITZERLAN Long Term: 0.02 mg/m3 - 0.004 ppm D MAK AUSTRIA Long Term: 0.1 mg/m3; Short Term: 0.2 mg/m3 - 0.008 ppm Predicted No Effect Concentration (PNEC) values vinyltrimethoxysilane; Exposure Route: Fresh Water; PNEC Limit: 0.34 mg/l Trimethoxyvinylsilane CAS: 2768-02-7 Exposure Route: Marine water; PNEC Limit: 0.034 mg/l Exposure Route: Freshwater sediments; PNEC Limit: 1.24 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0.12 mg/kg Exposure Route: Intermittent release; PNEC Limit: 3.4 mg/l Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l bis(1,2,2,6,6pentamethyl-4-piperidyl) sebacate; Decanedioic acid, bis(1,2,2,6,6pentamethyl-4piperidinyl) ester CAS: 41556-26-7 Exposure Route: Soil; PNEC Limit: 0.21 mg/kg Exposure Route: Intermittent release; PNEC Limit: 0.009 mg/l Exposure Route: Fresh Water; PNEC Limit: 0.0022 mg/l Exposure Route: Marine water; PNEC Limit: 0.000022 mg/l

Derived No Effect Level (DNEL) values

vinvltrimethoxysilane: Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Trimethoxyvinylsilane Worker Industry: 0.69 mg/kg; Consumer: 0.3 mg/kg CAS: 2768-02-7

Exposure Route: Freshwater sediments; PNEC Limit: 1.05 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0.11 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 4.9 mg/m3; Consumer: 1.04 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects Worker Industry: 2.5 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 2.5 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 2.35 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Worker Industry: 2.35 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 2.35 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects Consumer: 1.25 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects Consumer: 1.25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Consumer: 0.58 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects Consumer: 0.58 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects Consumer: 1.25 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Consumer: 1.25 $\rm mg/kg$

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Consumer: 0.58 mg/m3

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment. Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid Appearance and colour: paste beige Odour: characteristic Odour threshold: Not Relevant pH: Not Relevant Melting point / freezing point: Not Relevant Initial boiling point and boiling range: Not Relevant Flash point: 110 °C (230 °F) Evaporation rate: Not Relevant Upper/lower flammability or explosive limits: Not Relevant Vapour density: Not Relevant Vapour pressure: Not Relevant Relative density: 1.63 g/cm3 Solubility in water: insoluble Solubility in oil: partly soluble Partition coefficient (n-octanol/water): Not Relevant Auto-ignition temperature: Not Relevant Decomposition temperature: Not Relevant Viscosity: 120,000.00 mPA-s Kinematic viscosity: > 20,5 mm2/sec (40 °C) mm2/s Explosive properties: Not Relevant Oxidizing properties: Not Relevant Solid/gas flammability: Not Relevant Substance Groups relevant properties Not Relevant

Other information

Miscibility: Not Relevant Fat Solubility: Not Relevant Conductivity: Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions **Chemical stability** Data not available. Possibility of hazardous reactions None. **Conditions to avoid** Stable under normal conditions. Incompatible materials None in particular. Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1B(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Reproductive toxicity, Category 1B(H360)
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: Specific target organ toxicity following repeated exposure, Category 1(H372)
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

-	-	
vinyltrimethoxysilane;	 a) acute toxicity 	LD50 Oral Rat = 6899 mg/kg
Trimethoxyvinylsilane		

LD50 Skin Rat = 3158 mg/kg

silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg LD50 Skin > 2000 mg/kg
1-propanamine, 3- (trimethoxysilyl)-; 3- Aminopropyltrimethoxysil ane	a) acute toxicity	LD50 Oral Rat = 3010 g/kg
		LD50 Skin Rabbit = 11460 mg/kg
oxirane, 2-[[3- (diethoxymethylsilyl) propoxy]methyl]-; Diethoxy(3- glycidyloxypropyl) methylsilane	a) acute toxicity	LD50 Skin Rat > 2000 mg/kg
dibutyltin diacetyldiacetonate; Dibutylbis(pentane-2,4- dionato-0,0')tin	a) acute toxicity	LD50 Skin Rat > 2000 mg/kg
bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate; Decanedioic acid, bis(1,2,2,6,6- pentamethyl-4- piperidinyl) ester	a) acute toxicity	LD50 Oral Rat = 2615 mg/kg

Substance(s) listed on the IARC Monographs:

silica sand; quartz Group 1

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
1-propanamine, 3- (trimethoxysilyl)-; 3- Aminopropyltrimethoxysilane	CAS: 13822-56- 5 - EINECS: 237-511-5	a) Aquatic acute toxicity : LC50 Fish > 934 mg/L 96
		a) Aquatic acute toxicity: LC50 Daphnia = 331 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae > 1000 mg/L 72
		b) Aquatic chronic toxicity : NOEC Algae = 1.3 mg/L 72
dibutyltin diacetyldiacetonate; Dibutylbis(pentane-2,4-dionato- O,O')tin	CAS: 22673-19- 4 - EINECS: 245-152-0 -	a) Aquatic acute toxicity : LC50 Fish Oryzias latipes > 2 mg/L 96h ECHA

Print date

LC50 Inhalation Vapour Rat = 16.8 mg/l 4h

INDEX: 650-056-00-0

a) Aquatic acute toxicity : LC50 Fish Oryzias latipes > 2 mg/L 96h ECHA $\,$ - semi-static

bis(1,2,2,6,6-pentamethyl-4piperidyl) sebacate; Decanedioic 7 - EINECS: acid, bis(1,2,2,6,6-pentamethyl-4piperidinyl) ester CAS: 41556-26- a) Aquatic acute toxicity : EC50 Daphnia = 20 mg/L 24h 7 - EINECS: 255-437-1

a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 0.97 mg/L 96h

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

DOT-UN Number: Not Applicable ADR-UN number: Not Applicable IATA-Un number: Not Applicable IMDG-Un number: Not Applicable

UN proper shipping name

DOT-Proper Shipping Name: Not Applicable ADR-Shipping Name: Not Applicable IATA-Technical name: Not Applicable IMDG-Technical name: Not Applicable

Transport hazard class(es)

DOT-Hazard Class: Not Applicable ADR-Class: Not Applicable IATA-Class: Not Applicable IMDG-Class: Not Applicable

Packing group

DOT Packing Group: Not Applicable ADR-Packing Group: Not Applicable IATA-Packing group: Not Applicable

IMDG-Packing group: Not Applicable **Environmental hazards** Marine pollutant: No Environmental Pollutant: Not Applicable DOT-RQ: Not Applicable Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable Special precautions Department of Transportation (DOT): Not Applicable Road and Rail (ADR-RID) : Not Applicable Air (IATA): Not Applicable Sea (IMDG) : Not Applicable

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

vinyltrimethoxysilane; Trimethoxyvinylsilane	is listed in TSCA	Section 8b
silica sand; quartz	is listed in TSCA	Section 8b
1-propanamine, 3- (trimethoxysilyl)-; 3- Aminopropyltrimethoxysilane	is listed in TSCA	Section 8b
oxirane, 2-[[3- (diethoxymethylsilyl)propoxy] methyl]-; Diethoxy(3- glycidyloxypropyl)methylsilane	is listed in TSCA	Section 8b
dibutyltin diacetyldiacetonate; Dibutylbis(pentane-2,4-dionato- O,O')tin	is listed in TSCA	Section 8b Section 5
bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate; Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4- piperidinyl) ester	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

California Proposition 65

CWA listed substances:

No substances listed

USA - State specific regulations

Substance(s) listed under California Proposition 65:

Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

silica sand; quartz

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

silica sand; quartz

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

silica sand; quartz

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 7/19/2024 - version 2

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

H226Flammable liquid and vapour.H315Causes skin irritation.H317May cause an allergic skin reaction.H318Causes serious eye damage.H320Harmful if inhaled.H350May cause cancer.H360FDMay damage fertility. May damage the unborn child.H372Causes damage to organs through prolonged or repeated exposure.	Code	Description	
H317May cause an allergic skin reaction.H318Causes serious eye damage.H332Harmful if inhaled.H350May cause cancer.H360FDMay damage fertility. May damage the unborn child.	H226	Flammable liquid and vapour.	
H318Causes serious eye damage.H332Harmful if inhaled.H350May cause cancer.H360FDMay damage fertility. May damage the unborn child.	H315	Causes skin irritation.	
H332Harmful if inhaled.H350May cause cancer.H360FDMay damage fertility. May damage the unborn child.	H317	May cause an allergic skin reaction.	
H350May cause cancer.H360FDMay damage fertility. May damage the unborn child.	H318	Causes serious eye damage.	
H360FD May damage fertility. May damage the unborn child.	H332	Harmful if inhaled.	
	H350	May cause cancer.	
H372 Causes damage to organs through prolonged or repeated exposure	H360FD	May damage fertility. May damage the unb	orn child.
1372 Causes duringe to organis through profonged of repeated exposure.	H372	Causes damage to organs through prolonge	ed or repeated exposure.
H400 Very toxic to aquatic life.	H400	Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	H410	Very toxic to aquatic life with long lasting effects.	
Code Hazard class and hazard category Description	Code	Hazard class and hazard category	Description
A.1/4/Inhal Acute Tox. 4 Acute toxicity (inhalation), Category 4	A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.2/2 Skin Irrit. 2 Skin irritation, Category 2	A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1 Eye Dam. 1 Serious eye damage, Category 1	A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.4.2/1 Skin Sens. 1 Skin Sensitization, Category 1	A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B Skin Sens. 1B Skin Sensitization, Category 1B	A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.6/1A Carc. 1A Carcinogenicity, Category 1A	A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.7/1B Repr. 1B Reproductive toxicity, Category 1B	A.7/1B	Repr. 1B	Reproductive toxicity, Category 1B
A.9/1 STOT RE 1 Specific target organ toxicity following repeated exposure, Category 1	A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1 $% \left({{\left({{{\left({{{\left({{{\left({{{c}}} \right)}} \right)}} \right)}_{0}}} \right)}_{0}} \right)$
B.6/3 Flam. Liq. 3 Flammable Liquids — Category 3	B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
US-HAE/A1 Aquatic Acute 1 Acute aquatic hazard, category 1	US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/C1 Aquatic Chronic 1 Chronic (long term) aquatic hazard, category 1	US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 9. PHYSICAL AND CHEMICAL PROPERTIES